

---

**Product specifications for model 1533**


---

**Product Specifications, with reed switches or relays**

<b>sensor type</b>	diaphragm
<b>functions</b>	<b>gauge/switch, switch</b>
<b>min. range</b>	0-15 psid (0-5 psid with fluorosilicone diaphragm)
<b>max. range</b>	0-300 psid
<b>max. line pressure</b>	3000 psig
<b>min. burst pressure</b>	7000 psig, tested hydrostatically
<b>standard maximum temperature</b>	gauge/switch: 176°F standard, 150°F (plastic lens) switch: 176°F 140°F Relay
<b>high temp. construction</b>	N/A
<b>minimum temperature*</b>	<i>*Consult Factory for low-temperature applications.</i>
<b>calibration accuracy**</b>	±2% of full scale ascending after rap at room temperature <i>**Calibration accuracy is affected by temperature, and also by liquid-filling and follower-pointer options.</i>
<b>repeatability</b>	±2% of full scale
<b>switches/relay</b>	1 or 2 hermetically sealed reed switches or 1 relay in weatherproof enclosure
<b>switch adjustability</b>	upper 80% of full scale ascending (70% for B & C form switches in SST)
<b>switch dead band</b>	5-20% full scale
<b>certification</b>	NEMA 4X,IP65 <i>*Consult Factory for CE equivalent.</i>

**Standard configuration options, with reed switches or relays**

<b>configuration</b>	<b>unless otherwise specified</b>	<b>standard options available</b>
<b>porting size</b>	1/4" NPT	1/8" NPT, 1/2" NPT
<b>porting orientation</b>	in-line	N/A
<b>direction of pressure</b>	left to right	N/A
<b>calibration medium</b>	air	N/A
<b>switches &amp; relays</b>	(must be specified)	-A SPST N/O (120VAC,0.7A,70VA;200VDC,1.0A,50W) -B SPST N/C (120VAC,0.25A,5VA;175VDC,0.25A,5W) -C SPDT (120VAC,0.25A,5VA;175VDC,0.25A,5W) -R2 DPDT relay (contacts:120VAC,28VDC,10A coil:6 to 240VAC,6 to 110VDC)
<b>switch/relay setting</b>	set at top of range ascending	other set points within adjustability ascending or descending
<b>primary wetted parts</b>	(must be specified)	aluminum, 316SS
<b>secondary wetted parts</b>	range spring: 302SS magnet: ceramic	Teflon-coated spring and magnet
<b>static seals</b>	10 psid or below: fluorosilicone above 10 psid: buna-N	Viton, Teflon, silicone, EPDM, fluorosilicone
<b>diaphragm</b>	10 psid or below: fluorosilicone above 10 psid: buna-N	Viton, neoprene, EPDM, fluorosilicone, silicone
<b>lens</b>	glass	Plastic
<b>dial sizes</b>	(must be specified)	2.5", 3.5", 4.5", 6"
<b>dial case styles<sup>+</sup></b>	(must be specified)	"B" Basic Case (c-clamp not available) "F" Flanged Case (w/holes for panel mounting) (2.5" F-Style Ga. Case: N/A)
<b>starting mark on dial</b>	approximately 10% of full scale	N/A

---

**Product specifications for model 1533**


---

**Product Specifications, with transmitter**

<b>sensor type</b>	piston	
<b>functions</b>	<b>gauge/transmitter, transmitter (Loop powered)</b>	
<b>min. range</b>	0-5 psid	
<b>max. range</b>	0-150 psid	
<b>max. line pressure</b>	5000 psig	
<b>min. burst pressure</b>	15000 psig	
<b>standard maximum temperature</b>	gauge/transmitter:	200°F (glass lens), 150°F (plastic lens)
	transmitter:	200°F
<b>high temp. construction</b>	N/A	
<b>minimum temperature</b>	-20°F	
<b>calibration accuracy**</b>	±2% of full scale ascending after rap at room temperature	
	<i>**Calibration accuracy is compensated for temperature effects between -20 °F - 200 °F</i>	
<b>repeatability</b>	±2% of full scale	
<b>transducer enclosure</b>	weatherproof	
<b>certification</b>	CSA Class I, DIV. 2, Groups A, B, C & D; Class II, DIV. 2, Groups F & G (File 152872) NEMA 4X, IP65      *Consult factory for CE equivalent.	

**Standard configuration options, with transmitter**

<b>configuration</b>	<b>unless otherwise specified</b>	<b>standard options available</b>
<b>porting size</b>	1/4" NPT	1/8" NPT, 1/2" NPT, AND, MS
<b>porting orientation</b>	in-line	N/A
<b>direction of pressure</b>	left to right	N/A
<b>calibration medium</b>	all units with EPDM seals:    water all others: alum or SS:            hydraulic oil brass :                 water	N/A
<b>electronic outputs</b>	analog outputs: 4-20 mA (2 wire) 0-5 VDC (3 or 4 wire)	
<b>supply voltage</b>	9-35 VDC (reverse polarity protected)	
<b>loop resistance</b>	1300 ohms max. $R=((Vs-9)*1000)/20$ (ohms at Vs)	
<b>board connection</b>	1: + (EXC) 2: - 3: 0-5 V 4: COM	20-26 AWG wire
<b>conduit connection</b>	1/2" trade size	
<b>primary wetted parts</b>	(must be specified)	aluminum, 316SS, naval brass
<b>secondary wetted parts</b>	range spring: 302SS magnet: ceramic piston seal: Teflon	Teflon-coated spring and magnet
<b>static seals</b>	buna-N	Viton, Teflon, neoprene, EPDM, fluorosilicone
<b>lens</b>	glass	plastic
<b>dial sizes</b>	(must be specified)	2.5", 3.5", 4.5", 6"
<b>dial case styles<sup>+</sup></b>	(must be specified)	"B" Basic Case ( <i>C-clamp not available</i> ) "F" Flanged Case (w/holes for panel mounting)
<b>starting mark on dial</b>	approximately 10% of full scale	N/A