
Product specifications for model 2321

Product Specification (gauge, switch)

sensor type	variable-area
functions	Gauge, Gauge/Switch, Switch
min. range	0-1 GPM water, 4-30 SCFM compressed air (at 100 PSIG, 70°F)
max. range	0-10 GPM water, 10-100 SCFM compressed air (at 100 PSIG, 70°F)
max. line pressure	3000 psig
min. burst pressure	10000 psig
standard maximum temperature	gauge: 200°F standard, 150°F (plastic lens) gauge/switch: 176°F standard, 150°F (plastic lens) switch: 176°F
high temperature construction	gauge: 325°F (SST only, not available in aluminum or brass) gauge/switch, switch: N/A
minimum temperature*	<i>*Consult factory for low-temperature applications.</i>
calibration accuracy**	±2% of full scale ascending after rap at room temperature (for standard water & standard hydraulic oil) ±5% (for std. compressed air calibration) <i>**Calibration accuracy is affected by temperature, and also by liquid-filling and follower-pointer options.</i>
repeatability	±1% of full scale
switches	1 or 2 external hermetically sealed reed switches
switch adjustability	upper 80% of full scale ascending (70% for B & C form switches in SST)
switch dead band	5-20% full scale
certification	CSA (File 043810) <i>*Consult factory for CE equivalent.</i>

Standard configuration options (gauge, switch)

configuration	unless otherwise specified	standard options available
porting size	1/2" NPT	N/A
porting orientation	in-line	N/A
direction of flow	left to right	right to left (reverse porting), vertical flow up, vertical flow down
calibration medium	(must be specified) (Oil not available for EPDM units)	water (S.G.=1, Vis.=1 CS) hydraulic oil (S.G.=.86, Vis.=78 CS) compressed air (100 PSIG, 70°F)
switches	(must be specified)	-A SPST N/O (120VAC,0.7A,70VA;200VDC,1.0A,50W) -B SPST N/C (120VAC,0.25A,5VA;175VDC,0.25A,5W) -C SPDT (120VAC,0.25A,5VA;175VDC,0.25A,5W)
switch setting	set at top of range ascending	other set points within adjustability ascending or descending
primary wetted parts	(must be specified)	aluminum, 316SS, naval brass
secondary wetted parts	range spring: 302SS magnet: Teflon-coated ceramic metering cone: Delrin	Teflon-coated spring, Teflon metering cone
static seals	buna-N, Viton for high temp.	Viton, Teflon, neoprene, EPDM, fluorosilicone
lens	glass	plastic
dial sizes	(must be specified)	2.5", 3.5", 4.5", 6"
dial case styles⁺	(must be specified)	"B" Basic Case (c-clamp available on all but 2.5") "F" Flanged Case (w/holes for panel mounting)
starting mark on dial	approximately 10% of full scale	N/A